

ACR1252U

USB NFC Reader III



Specification

Physical Characteristics

Dimensions	98.0 mm (L) × 65.0 mm (W) × 12.8 mm (H)
Weight.....	81 g
Color	Matte Black

USB Host Interface

Protocol.....	USB CCID
Connector Type.....	Standard Type A
Power Source.....	From USB port
Speed.....	USB Full Speed (12 Mbps)
Supply Voltage.....	5 V
Supply Current	Max. 200 mA
Cable Length.....	1.0 m, Fixed

Contactless Smart Card Interface

Standard	ISO/IEC 18092 NFC, ISO 14443 Type A & B, MIFARE, FeliCa
Protocol.....	ISO 14443 T=CL for ISO 14443-4-compliant cards T=CL Emulation for MIFARE Classic, ISO 18092, FeliCa and NFC tags
Operating Frequency	13.56 MHz
Operating Distance	Up to 50 mm (depending on tag type)
Smart Card Read/Write Speed.....	106 Kbps, 212 Kbps, 424 Kbps
Antenna Size.....	50 mm × 40 mm

SAM Card Interface

Number of Slot 1 Standard SIM-sized Card Slot
Standard ISO 7816, Class A (5 V)
Protocol T=0; T=1
Smart Card Read/Write Speed 9.6 Kbps – 215 Kbps
Card Connector Type SAM Slot 0: Contact

Built-in Peripheral

LED 1 bi-color: Red and Green
Buzzer Monotone

Application Programming Interface

PC-linked Mode PC/SC
..... CT-API (through wrapper on top of PC/SC)

Other Feature

Firmware Upgrade Supported

Operating Conditions

Temperature 0 °C – 60 °C
Humidity Max. 90% (non-condensing)
MTBF 500,000 hrs

Certifications/Compliance

EN 60950/IEC 60950, ISO 18092, ISO 14443, ISO 7816 (SAM Slot), USB Full Speed, NFC Forum Certification, Felica Performance Certification, PC/SC, CCID, CE, FCC, RoHS, REACH J-LIS (Japan), VCCI (Japan), MIC (Japan), KC (Korea), Microsoft® WHQL

Device Driver Operating System Support

Windows® CE 5.0, Windows® CE 6.0, Windows® Embedded Compact 7, Windows® XP, Windows® Vista™, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10 Windows® Server 2003, Windows® Server 2003 R2, Windows® Server 2008, Windows® Server 2008 R2, Windows® Server 2012, Windows® Server 2012 R2, Windows® 2016 Linux®, Mac OS®, Solaris, Android™ 3.1 and later

บริษัท อีซี คอนเนคชัน จำกัด

Tel. 090-401-1144, 02-910-0411



@econneC