

ACR123U

Intelligent Contactless Reader



Specification

Physical Characteristics

Dimensions	Main Body: 159 mm (L) × 100 mm (W) × 21 mm (H)
.....	With Stand: 177.4 mm (L) × 100.0 mm (W) × 94.5 mm (H)
Weight.....	Main Body: 281 g
.....	With Stand: 506 g
Color	Black

Processor

Core	ARM 32-bit Cortex-M3 CPU
------------	--------------------------

USB Host Interface

Protocol.....	USB CCID
Connector Type.....	Standard Type A
Power Source.....	From USB port
Speed.....	USB Full Speed (12 Mbps)
Supply Voltage.....	5 V
Supply Current	Max. 200 mA
Cable Length.....	1.5 m, Fixed

Contactless Smart Card Interface

Standard	ISO 14443-4 Type A and B Parts 1-4
Protocol.....	ISO 14443 T=CL for ISO 14443-4-compliant cards
.....	T=CL Emulation for MIFARE Classic
Operating Frequency	13.56 MHz
Operating Distance	Up to 50 mm (depending on tag type)
Smart Card Read/Write Speed.....	106 Kbps, 212 Kbps, 424 Kbps, 848 Kbps
Antenna Size.....	75 mm × 75 mm

SAM Card Interface

Number of Slots	3 Standard SIM-sized Card Slots
Standard	ISO 7816, Class A, B, C (5 V, 3 V, 1.8 V)
Protocol.....	T=0; T=1
Smart Card Read/Write Speed.....	9.6 Kbps – 344 Kbps
Card Connector Type.....	SAM Slot 0: Contact
.....	SAM Slot 1: Contact
.....	SAM Slot 2: Contact

Built-in Peripheral

LCD.....	Graphic LCD with white backlight
.....	128 pixels × 64 pixels
.....	Number of characters: 16 characters × 8 lines
LED.....	4 single-color: Blue, Yellow, Green, and Red
Speaker.....	Audio tone indication
Tapping Region.....	Tri-color backlight: Red, Green and Blue

Application Programming Interface

PC-linked Mode.....	PC/SC
.....	CT-API (through wrapper on top of PC/SC)

Other Feature

Firmware Upgrade	Supported
------------------------	-----------

Operating Conditions

Temperature	0 °C – 60 °C
Humidity	Max. 90% (non-condensing)
MTBF	240,000 hrs

Certifications/Compliance

ISO 14443, ISO 7816 (SAM Slot), PC/SC, CCID, CE, FCC, RoHS, REACH VCCI (Japan), KC (Korea), Microsoft® WHQL

Device Driver Operating System Support

Windows® CE 5.0, Windows® CE 6.0, Windows® Embedded Compact 7, Windows® XP, Windows® Vista™, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10 Windows® Server 2003, Windows® Server 2003 R2, Windows® Server 2008, Windows® Server 2008 R2, Windows® Server 2012, Windows® Server 2012 R2, Windows® 2016 Linux®, Mac OS®, Solaris, Android™ 3.1 and later

บริษัท อีซี คอนเนคชั่น จำกัด

Tel. 090-401-1144, 02-910-0411



@econnec